

Type	SM-03M	SM-06M	SM-09M	SM-12M
Humid vol per hour	3kg/h	6kg/h	9kg/h	12kg/h
Controllable humidity range	±3%RH	±3%RH	±3%RH	±3%RH
Max power	250w	300w	350w	500w
Power	220v-50Hz	220v-50Hz	220v-50Hz	220v-50Hz
Humidity controllable range	RH30-95%	RH30-95%	RH30-95%	RH30-95%
Humidity adjustable range	RH10-95%	RH10-95%	RH10-95%	RH10-95%
Water tank capacity	35L	35L	30L	30L
Applicable area	20m²-30m²	30m²-60m²	90m²-100m²	100m²-120m²
Anion function	Yes	Yes	Yes	Yes
Adjustable wind speed	Yes	Yes	Yes	Yes
Overflow protection function	Yes	Yes	Yes	Yes
Water inlet method	Auto&Manual switchable			
Net weight	25kg	30kg	70kg	80kg
Size (L*W*H)	430*600*1150mm	430*600*1150mm	728*486*1640mm	728*486*1640mm

Type	SM-15M	SM-20M	SM-30M	SM-40M
Humid vol per hour	15kg/h	20kg/h	30kg/h	40kg/h
Controllable humidity range	±3%RH	±3%RH	±3%RH	±3%RH
Max power	700w	900w	1300w	1500w
Power	220v-50Hz	220v-50Hz	380v-50Hz	380v-50Hz
Humidity controllable range	RH30-95%	RH30-95%	RH30-95%	RH30-95%
Humidity adjustable range	RH10-95%	RH10-95%	RH10-95%	RH10-95%
Water tank capacity	40L	40L	40L	50L
Applicable area	120m²-150m²	150m²-200m²	200m²-300m²	300m²-420m²
Anion function	Yes	Yes	Yes	Yes
Adjustable wind speed	Yes	Yes	Yes	Yes
Overflow protection function	Yes	Yes	Yes	Yes
Water inlet method	Auto&Manual switchable			
Net weight	95kg	100kg	150kg	165kg
Size (L*W*H)	882*486*1640mm	1082*486*1640mm	1624*550*1750mm	1624*550*1750mm